

## **General Disclaimer**

### **One or more of the Following Statements may affect this Document**

- This document has been reproduced from the best copy furnished by the organizational source. It is being released in the interest of making available as much information as possible.
- This document may contain data, which exceeds the sheet parameters. It was furnished in this condition by the organizational source and is the best copy available.
- This document may contain tone-on-tone or color graphs, charts and/or pictures, which have been reproduced in black and white.
- This document is paginated as submitted by the original source.
- Portions of this document are not fully legible due to the historical nature of some of the material. However, it is the best reproduction available from the original submission.

No 100


MSC INTERNAL NOTE MSC-CF-R-68-1

RESULTS OF SIMULATION OF  
LM RENDEZVOUS USING GRAPHICAL CHARTS

Prepared by: John E. Hutchins  
John E. Hutchins  
Flight Procedures Section

Authorized for Distribution

Warren J. North  
Warren J. North  
Chief, Flight Crew Support Division



NATIONAL AERONAUTICS AND SPACE ADMINISTRATION  
MANNED SPACECRAFT CENTER  
HOUSTON, TEXAS

February 8, 1968

FACILITY FORM 602

(ACCESSION NUMBER) - 34768

(PAGES) 31

(NASA CR OR TMX OR AD NUMBER) TMX 64339

MSC INTERNAL NOTE MSC-CF-R-68-1

RESULTS OF SIMULATION OF  
LM RENDEZVOUS USING GRAPHICAL CHARTS

Approved by: David D. Lang  
David D. Lang  
Chief, Flight Procedures Section

Paul C. Kramer  
Paul C. Kramer  
Chief, Crew Safety and Procedures Branch

J. W. Bilodeau  
James W. Bilodeau  
Assistant Chief for Crew Integration

W. J. North  
Warren J. North  
Chief, Flight Crew Support Division

February 8, 1968

## TABLE OF CONTENTS

- 1.0 SUMMARY
- 2.0 INTRODUCTION
  - 2.1 Assumptions
  - 2.2 Subjects
  - 2.3 Initial Conditions
  - 2.4 Procedures
  - 2.5 Backup Charts
    - 2.5.1 TPI Charts
    - 2.5.2 M/C Charts
- 3.0 DISCUSSION
  - 3.1 Propellant Usage
    - 3.1.1 TPI
    - 3.1.2 M/C's
    - 3.1.3 Braking and LOS Control
  - 3.2 Accuracy of Charts
- 4.0 CONCLUSIONS



## 1.0 SUMMARY

A man-in-the-loop simulation study of LM terminal phase rendezvous in earth orbit was conducted on the Lunar Module Procedures Simulator (LMPS) to establish the adequacy of graphical rendezvous charts as a backup and monitor of the PGNS and AGS. A total of 30 runs were made with 6 sets of initial conditions starting approximately 14 minutes prior to terminal phase initiation, and ending after establishing formation flying at a range of 50 to 100 feet. The resulting data indicated the mean propellant quantity required to accomplish a 15 n.m.  $\Delta h$  rendezvous from below to be 126.8 pounds, with a maximum propellant requirement of 150.3 pounds and a minimum of 112.1 pounds. Assuming a statistically normal distribution of propellant resulted in a computed standard deviation of 15.5 pounds in the total propellant used.

## 2.0 INTRODUCTION

### 2.1 Assumptions

The simulation runs were based on the following assumptions:

(1) Near inplane conditions existed at TPI.

(2) Information available for performing maneuvers was as follows:

<u>DATA</u>	<u>SYMBOL</u>	<u>SOURCE/DISPLAY</u>	<u>SYSTEM ERRORS</u>
Pitch angle	$\Theta \sim .01 \text{ DEG}$	AGS DEDA	None
Body axis velocity increments	$\Delta V_{x, y, z}$ $\sim \text{FPS}$	AGS DEDA	None
Range	$R, \text{NM/FT}$	RR Tapemeter	$\pm 0.5 \text{ NM}$ random $R < 10$
Range rate	$\dot{R}, \text{FPS}$	RR Tapemeter	2 FPS bias $R < 50 \text{ FPS}$
Target line-of-sight rates	$\dot{\Theta}_I, \dot{\Psi}_I$ $\sim \text{m RAD/SEC}$	RR Crosspointers	None

(3) All thrusting was done along the LOS and/or normal to the LOS.

(4) The only AGS data used was Address 307 (the positive angle between the  $+Z_{LM}$  axis and local horizontal).

(5) The AGS autopilot provided attitude hold and pulse mode for control.

### 2.2 Subjects

The simulations were run by two teams consisting of two simulation subjects each who alternated in the roles of left and right-hand pilots.

### 2.3 Initial Conditions

Six sets of initial conditions (IC's) were used--a nominal set with the LM and CSM in 165 n.m. and 180 n.m. circular orbits, respectively, and five other sets incorporating various errors in the LM state vector (see Figure 1). Neither out-of-plane velocity nor out-of-plane displacement were incorporated in any of the IC's. The LM configuration was the full ascent stage with full RCS tanks, giving it a total weight of 11,860 pounds. In this configuration, 1 pound of RCS propellant was equivalent to 0.73 FPS characteristic velocity.

### 2.4 Procedures

In calculating the TPI solution, the left-hand pilot used pulse mode to acquire and boresight on the CSM, then the right-hand pilot read elevation angle (Address 307) from the DEDA. Nominally, an elevation angle of 19.36 degrees occurred at TPI-8 minutes. The Event Timer (ET) was set to 8 minutes counting down and started when 307 indicated 019.36 degrees. The left-hand pilot boresighted on the CSM again at TPI-5 minutes and range and range rate were taken from the tapemeter while elevation angle was read from the DEDA. These data were then used to compute a TPI solution from the backup chart (see Appendix).

Attitude hold was used during thrusting with the pilot returning to pulse mode after thrusting was terminated.

The ET was set to count up when  $t = 0$  and the midcourse backup charts were used to compute M/C corrections based on LOS angle data and range and range rate data taken at the times after TPI specified on the M/C charts.

After the second M/C correction, the X-pointers were used to null LOS and azimuth rates. Braking was done according to the gates shown in Figure 2.

## 2.5 Backup Charts

### 2.5.1 TPI Chart

The TPI backup chart consisted of a plot of range and range rate versus  $\Delta V$  forward and another of  $\Delta \theta$  and range versus  $\Delta V$  up/down from which an inplane TPI burn was computed based on the backup data taken. The  $\Delta \theta$  used was the (positive) change in the LOS angle from TPI-8 minutes to TPI-5 minutes.

### 2.5.2 M/C Charts

Two types of backup M/C charts were used. Both are shown in the Appendix. The first type required that the LOS angle  $\theta$  be read at 4,  $4\frac{1}{2}$ ,  $7\frac{1}{2}$ , and 8 minutes after TPI for the first M/C and at 15,  $15\frac{1}{2}$ ,  $18\frac{1}{2}$ , and 19 minutes after TPI for the second M/C. Range and range rate data were taken at 6 and 17 minutes after TPI for each of the two M/C's. For each M/C, the difference in the sums of the first two and last two

LOS angle readings was calculated to get an "average"  $2 \Delta \theta$ . This was done to reduce the effects of tracking errors. This was used in a plot of  $2 \Delta \theta$ , range, and the last value of  $\theta$  taken versus  $\Delta V$  up/down to get an up/down correction. The fore/aft correction was computed from a plot of range and  $\theta$  versus  $\Delta V$  fore/aft. The second type of M/C chart used was similar to the TPI chart in that it required only two measurements of  $\theta$  LOS (one at TPI+15 minutes and the other at TPI+18 minutes) and one reading each of range and range rate (taken at the second reading of  $\theta$  LOS). Otherwise, the graphical solutions for  $\Delta V$  fore/aft and  $\Delta V$  up/down were similar to those used on the other type of chart. Where this second type of backup M/C chart was used, only one M/C correction was made.



### 3.0 DISCUSSION

#### 3.1 Propellant Usage

A total of 19 familiarization runs and 30 data runs were made during the study. The familiarization runs are not included in the results since they were made to develop pilot proficiency. Figure 3 is a breakdown of the mean propellant requirements for each of the six cases individually and the six cases as a whole. The theoretical minimum propellant usage is the two-impulse burn as computed by the AGS computer. A summary of the results of the simulations in terms of total propellant used is also given in Figure 4. Case I required the greatest amount of propellant, while Case IV was the most economical. This was due to the LM being below its nominal altitude with its altitude decreasing in Case I; whereas in Case IV, the LM was over a mile higher than nominal and slowly losing altitude. The remaining IC's represented various cases between these two extremes.

##### 3.1.1 TPI

The propellant required for TPI by the various cases is given in Figure 5. Note that only Case IV showed a consistent trend to deviate from the mean TPI propellant requirement, the trend being to require less than the nominal amount of propellant. This would be expected with the  $\Delta h$  at TPI being less than nominal for Case IV.

### 3.1.2 M/C's

Figures 6 and 7 are graphic representations of the propellant requirements for the M/C's that were made. The mean M/C correction in terms of pounds of propellant is given on each figure. The ellipses were generated using the formula for the standard deviation of data about the mean value. The graphs use the sign convention that up and forward are positive burns with aft and down representing negative burns. For instance, the mean first M/C burn was 1.3 pounds up and 0.2 pounds aft, and the mean second M/C burn was 1.9 pounds up and 0.9 pounds forward.

### 3.1.3 Braking and LOS Control

The propellant requirements for braking and for nulling of LOS rates are given in Figures 8 and 9. LOS control consisted of nulling elevation and azimuth rates as indicated by the crosspointers, and the data of Figure 9 are totals required to null both rates. The braking gates given in Figure 2 were utilized by all of the simulator subjects. Wide variations in the quantity of propellant for braking can be noted in each case, but Case V was consistently less expensive than any other. Likewise, there was a wide variation in each case of the propellant required to control LOS rates with Case IV being far cheaper than any other case.

### 3.2 Accuracy of Charts

The charts used in this study proved to be an adequate means of computing a TPI and M/C burns independently of the PGNS and AGS. However, the charts were susceptible to various errors that limit their solutions to an accuracy of  $\pm 1$  FPS. Errors in the measurement of LOS angle are a function of the precision with which the pilot can boresight on the target which is on the order of  $\pm 0.1$  degrees using the error needles. Also, while the range rate tapemeter could be read accurately to within 0.5 FPS, the range tapemeter could only be read to the nearest 0.5 n.m. on the largest scale and to within 100 feet on the intermediate scale. The error in  $\theta$  LOS when boresighting represented an uncertainty of 1 FPS UP/DWN at TPI and at the M/C's. The error in reading range was equivalent to an uncertainty of 2 FPS in the first M/C and 0.5 FPS in the second M/C. Additional errors in range data were caused by a tendency of the range tapemeter to slip when driven to the reset point. Frequent checks on the tapemeter were made from within the crew station, and several times it was found to be off by 0.5 n.m. at the point in the run where the first M/C was being computed. The error due to slippage became less critical, however, as the tapemeter progressed to the intermediate and lower scales. The presence of these uncertainties in the backup charts led to the decision not to apply any computed burns of 1 FPS or less.

#### 4.0 CONCLUSIONS

The simulation study made led to the following conclusions:

- (1) The charts and procedures used consistently resulted in a successful LM terminal phase rendezvous.
- (2) The mean propellant required for terminal phase was 126.8 pounds, and it was felt that with more experience on the part of the simulator subjects this total could be reduced perhaps as much as 10 pounds.
- (3) Corrections of 1 FPS or less should not be applied.
- (4) The mean value of TPI was 44.5 pounds along the line-of-sight.
- (5) The mean value of the first M/C was 1.3 pounds up and 0.3 pounds aft.
- (6) The mean value of the second M/C was 0.8 pounds forward and 1.9 pounds up.

FIGURE 1  
INITIAL CONDITIONS

<u>CASE</u>	<u>R(NM)</u>	<u><math>\dot{R}</math>(F/S)</u>	<u><math>\theta_{LOS}</math> (DEG)</u>	<u><math>H_{LM}</math> (NM)</u>	<u><math>\dot{H}_{LM}</math> (F/S)</u>
NOM	52.9	-151.0	16.0	165.0	0.0
I	52.8	-153.6	16.7	164.4	-2.1
II	54.4	-166.0	17.1	163.5	1.8
III	52.1	-154.9	16.7	164.5	-2.8
IV	46.1	-136.5	16.9	166.2	-0.3
V	53.12	-163.8	17.3	163.7	3.8






FIGURE 2


MEAN PROPELLANT USAGE (LBS.)

CASE:		NOM	I	II	III	IV	V	ALL CASES
TPI:	fore	43.6	46.1	47.5	45.9	38.9	45.0	44.6
	aft	0.0	0.0	0.0	0.0	0.0	0.0	0.0
	up	0.0	2.6	0.6	1.7	0.0	0.0	0.8
	down	0.0	0.0	1.4	0.0	0.0	1.7	0.6
M/C 1:	fore	1.3	4.0	1.2	0.5	1.6	0.5	1.5
	aft	1.1	0.0	2.2	0.9	0.0	5.0	1.7
	up	2.0	4.7	1.3	2.5	0.0	0.1	1.6
	down	0.0	0.0	0.3	0.0	0.3	1.2	0.3
M/C 2:	fore	2.9	7.6	0.3	2.5	3.7	0.8	2.9
	aft	0.0	0.0	5.3	1.9	1.0	3.6	2.1
	up	1.4	8.5	1.9	0.6	2.3	0.1	2.5
	down	0.0	0.0	0.5	0.6	1.1	1.3	0.6
BRAKING:		42.3	34.6	34.3	41.9	37.2	23.9	35.3
LOS	up	NA	NA	NA	NA	NA	NA	NA
CONTROL:	down	NA	NA	NA	NA	NA	NA	NA
	left	NA	NA	NA	NA	NA	NA	NA
	right	NA	NA	NA	NA	NA	NA	NA
ATTITUDE:		25.0	23.8	23.4	17.0	23.4	24.6	22.7
TOTAL FUEL:		119.1	150.3	131.6	122.6	112.1	122.6	126.3
THEORETICAL MINIMUM:		0.0	96.0	13.3	89.3	82.6	12.0	10.2
DIFFERENCE:		31.1	54.3	38.3	33.3	29.5	30.6	36.6
FACTOR:*		1.4	1.6	1.4	1.4	.4	1.3	1.4
TRANSFER TIME:		4:23.4	4:7:16	4:3:07	4:0:15	4:0:52	4:6:02	4:3:22


\*/ FACTOR = TOTAL FUEL/THEORETICAL MINIMUM

FIGURE 3











$\Delta_{(1.2, 10.0)}$

1st M/C PROPELLANT (LBS.)




FIGURE 6



(10.8, 19.1)  
(17.3, 9.4)

(0, 10.5)

2nd M/C PROPELLANT (LBS.)

165 MP/1000W


165 FOSE/NET

FIGURE 7

CASE

NOMINAL


1 2 3 4 5 6











# APPENDIX

ATT CONT - PULSE (3)  
 RATE/ERRMON - RNDZ RADAR  
 X-TRANSL - 2 JETS  
 MAN THROT - CDR  
 THR CONT - MAN  
 BAL CPL - ON  
 THROTTLE/JET - JET

Enter 407:+00000, 407:10000, 410:50000  
 (External  $\Delta V$ )  
 Enter 450:; 451:; 452: = +00000  
 Readout 307: (e)

Set E.T. to -8:00 to Count Down  
 When 307: 18.5 Deg, Boresight With  
 Precision - Reticule or Error Needles

-8:00 When 307: = 19.36 Deg, Give CP Mark, Start  
 E.T. Down, Copy

-5:00 Give Pilot Mark Read 307: (e), R and R  
 From T.M., Copy

-0:30 ATT CONT - MODE CONT (3)  
 MODE CONTROL - ATT HOLD  
 Readout 502: ( $\Delta VZ$ )

0:00 Start FWD Thrust AT = 0:00  
 Start E.T. Counting Up  
 Give CP Mark When  $\Delta VZ$  Attained

Readout 500:  
 Thrust Up/Down  
 Give CP Mark When  $\Delta Vx$  Attained  
 ATT CONT - PULSE (3)

# TERMINAL PHASE INITIATION

PT TIME  $\Theta$   $\Theta_{NOM}$  R  $R_{NOM}$   $\dot{R}$   $\dot{R}_{NOM}$



A -8:00 19.36 44.4 148.2

B -5:00 -21.63 40.1 146.0

$-\Delta\Theta$  2.27

TPI 000

AXIS	DIR	$\Delta V$	$\Delta T$	USED
Z	FWD	---	---	---
X	U-D	---	---	---





Boresight on Target with Reticle or Error  
Needles

Enter 407:+00000, 407:+10000

4:00 Readout 307: (e) Copy

4:30 Readout 307: (e) Copy, Compute  $2\theta_1$

6:00 Read R and R From T.M. Copy

7:30 Readout 307: (e) Copy


8:00 Readout 307: (e) Copy  
Compute  $\Delta V_x$ ,  $\Delta V_z$   
Readout 502: ( $\Delta VZ$ )

ATT CONT - MODE CONTROL (3)  
Thrust F/A ASAP

Give CP Mark When  $\Delta VZ$  Attained  
Readout 500: ( $\Delta VX$ )

Give CP Mark When  $\Delta VX$  Attained

ATT CONT - PULSE (3)





Boresight on Target With Reticle or Error  
Needles

Enter 407:+00000, 4C7:+10000

15:00 Readout 307: (e) Copy

15:30 Readout 307: (e) Copy, Compute  $2\theta_1$

17:00 Read R and R From T.M. Copy

18:30 Readout 307: (e) Copy

19:00 Readout 307: (e) Copy  
Compute  $\Delta V_x, \Delta V_z$   
Readout 502: ( $\Delta V_z$ )

ATT CONT - MODE CONTROL (3)  
Thrust F/A ASAP

Give CP Mark When  $\Delta V_z$  Attained  
Readout 500: ( $\Delta V_x$ )

Give CP Mark When  $\Delta V_x$  Attained



ATT CONT - PULSE (3)



# SECOND CORRECTION

TIME	$\theta$	$\theta_{NOM}$	R	$R_{NOM}$	$R$	$R_{NOM}$
15:00		54.3		11.7		106.3
15:30		55.7		11.2		103.3
201		110.0				
17:00		60.0		58,895		94.1
18:30		64.8		50,837		85.0
19:00		66.5		48,331		82.0
202		131.3				
201		110.0				
202		21.3				

AXIS	DIR	$\Delta V$	$\Delta T$	USED
Z	F-A			
X	U-D			



UP  
DOWN  
 $\Delta T$  (SEC)

# SECOND CORRECTION

TIME :  $\theta$  :  $\theta_{NOM}$  :  $R$  :  $R_{NOM}$  :  $\dot{R}$  :  $\dot{R}_{NOM}$

15:00 : 52.96 : 12.2 : 55200 : 109.00

18:00 : 61.60 : 90.04


$\Delta \theta$  : 8.64

$\dot{R}_{REQ}$  \_\_\_\_\_

$\dot{R}_{18:00} =$  \_\_\_\_\_


$\Delta V_Z$  \_\_\_\_\_

AXIS	DIR	AV	$\Delta T$	USED
Z	F-A	_____	_____	_____
X	U-D	_____	_____	_____





# LM RENDEZVOUS FROM BELOW RELATIVE REFERENCE TRAJECTORY



Boresight on Target With Reticule or Error  
Needles

Enter 407:+00000, 407:+10000

15:00 Readout 307: (e) Copy

15:30 Readout 307: (e) Copy, Compute  $2\theta_1$

17:00 Read R and R From T.M. Copy

18:30 Readout 307: (e) Copy

19:00 Readout 307: (e) Copy  
Compute  $\Delta V_x, \Delta V_z$   
Readout 502: ( $\Delta V_z$ )

ATT CONT - MODE CONTROL (3)  
Thrust F/A ASAP

Give CP Mark When  $\Delta V_z$  Attained  
Readout 500: ( $\Delta V_x$ )

Give CP Mark When  $\Delta V_x$  Attained

ATT CONT - PULSE (3)